



SAFETY DATA SHEET

Tensorgrip G67 Water-Based Pressure Sensitive Flooring Adhesive Canister

1. Identification

Product identifier

Product name Tensorgrip G67 Water-Based Pressure Sensitive Flooring Adhesive Canister

Product number USA

Recommended use of the chemical and restrictions on use

Application Canister Spray Adhesive

Details of the supplier of the safety data sheet

Supplier Quin Global US, Inc.
5710 F St
Omaha NE 68117
(402) 731 3636
(402) 731 1473
marketing.us@quin-global.com

Emergency telephone number

Emergency telephone Chemtrec: 1 800 424 9300

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Aerosol 3 Press. Gas, Compressed - H280

Health hazards Eye Irrit. 2A - H319

Environmental hazards Not Classified

Human health The liquid may be irritating to eyes, respiratory system and skin. Symptoms following overexposure may include the following: Headache. Dizziness. Nausea, vomiting.

Label elements

Pictogram



Signal word Warning

Hazard statements H280 Contains gas under pressure; may explode if heated.
H319 Causes serious eye irritation.

Tensorgrip G67 Water-Based Pressure Sensitive Flooring Adhesive Canister

Precautionary statements	<p>P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.</p> <p>P251 Pressurized container: Do not pierce or burn, even after use</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P412 Do not expose to temperatures exceeding 50°C/122°F.</p>
---------------------------------	--

Supplemental label information	AT(i) 2.517% of the mixture consists of ingredient(s) of unknown acute inhalation toxicity.
---------------------------------------	---

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

1,1,1,2 Tetrafluoroethane (134a)	5-10%
CAS number: 811-97-2	
Classification	
Press. Gas, Liquefied - H280	
Acute Tox. 4 - H332	
Simple Asphyxiant - USH03	

Proprietary Polymers	1-5%
CAS number: —	
Classification	
Acute Tox. 4 - H302	
Acute Tox. 4 - H312	

The full text for all hazard statements is displayed in Section 16.

4. First-aid measures

Description of first aid measures

General information	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention.
Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention.
Skin Contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove any contact lenses and open eyelids wide apart. Only remove contact lenses if the person is conscious, coherent and they can remove them themselves. If adhesive bonding occurs, do not force eyelids apart. Continue to rinse for at least 15 minutes. If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical personnel.

Tensorgrip G67 Water-Based Pressure Sensitive Flooring Adhesive Canister

Most important symptoms and effects, both acute and delayed

Inhalation	May cause coughing and difficulties in breathing. May cause eye and respiratory system irritation. Overexposure may depress the central nervous system, causing dizziness and intoxication.
Ingestion	Aspiration hazard if swallowed. May be fatal if swallowed and enters airways. Ingestion may cause severe irritation of the mouth, the esophagus and the gastrointestinal tract. May Cause the following effects: Gastrointestinal symptoms, including upset stomach. Central nervous system depression. Nausea, vomiting. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
Skin contact	May be absorbed through the skin. Product has a defatting effect on skin. The product is irritating to eyes and skin. A single exposure may cause the following adverse effects: Dryness and/or cracking.
Eye contact	Causes serious eye irritation. Burns can occur. A single exposure may cause the following adverse effects: Pain. Conjunctivitis, irritation, tearing. Prolonged or repeated exposure may cause the following adverse effects: Irritation of eyes and mucous membranes. Prolonged contact causes serious eye and tissue damage.

5. Fire-fighting measures

Special hazards arising from the substance or mixture

Specific hazards	Pressurized container: Must not be exposed to temperatures above 50°C/120°F Containers can burst violently or explode when heated, due to excessive pressure build-up.
-------------------------	--

Advice for firefighters

Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
--	---

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	For personal protection, see Section 8.
-----------------------------	---

Environmental precautions

Environmental precautions	Avoid discharge into drains. Contain spillage with sand, earth or other suitable non-combustible material.
----------------------------------	--

Methods and material for containment and cleaning up

Methods for cleaning up	Stop leak if possible without risk. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.
--------------------------------	--

7. Handling and storage

Precautions for safe handling

Usage precautions	Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level. Container must be kept tightly closed when not in use.
--------------------------	---

Advice on general occupational hygiene	Do not eat, drink or smoke when using this product.
---	---

Conditions for safe storage, including any incompatibilities

Tensorgrip G67 Water-Based Pressure Sensitive Flooring Adhesive Canister

Storage precautions Keep away from heat, sparks and open flame. Keep container tightly closed. Keep only in the original container. Pressurized container: Must not be exposed to temperatures above 50°C/120°F

8. Exposure controls/Personal protection

Control parameters

Occupational exposure limits

1,1,1,2 Tetrafluoroethane (134a)

Long-term exposure limit (8-hour TWA): WEEL:US.AIHA = Workplace Environmental Exposure Level Guides 4240 mg/m³
1000 ppm

Exposure controls

Protective equipment



Appropriate engineering controls

This product must not be handled in a confined space without adequate ventilation. Provide adequate general and local exhaust ventilation.

Eye/face protection

Wear chemical splash goggles.

Hand protection

Use protective gloves.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

Respiratory protection

Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. If exposure levels are likely to be exceeded, use a half face mask fitted with an organic vapor filter for short term low level exposures. For long term or high level exposures, a supplied air respirator should be used.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Aerosol.
Color	White / off-white.
Odor	Mild. Musty (mouldy).
Relative density	1.28
Solubility(ies)	Water soluble when wet
Volatile organic compound	This product contains a maximum VOC content of 0 g/l.

10. Stability and reactivity

Stability

Stable at normal ambient temperatures and when used as recommended.

Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with the following materials:
Oxidizing agents. Reducing agents.

Tensorgrip G67 Water-Based Pressure Sensitive Flooring Adhesive Canister

Hazardous decomposition products Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂). Nitrous gases (NO_x).

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 19,864.92

Acute toxicity - dermal

ATE dermal (mg/kg) 43,702.82

Acute toxicity - inhalation

ATE inhalation (gases ppm) 53,571.43

Toxicological information on ingredients.

1,1,1,2 Tetrafluoroethane (134a)

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ gases ppmV) 500,000.0

Species Rat

ATE inhalation (gases ppm) 4,500.0

Skin Contact Contact with liquid form may cause frostbite.

Proprietary Polymers

Acute toxicity - oral

ATE oral (mg/kg) 500.0

Acute toxicity - dermal

ATE dermal (mg/kg) 1,100.0

12. Ecological information

13. Disposal considerations

Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

14. Transport information

Air transport notes 1. <75kg, 2. <150kg

UN Number

UN No. (TDG) 3500

UN No. (ICAO) 3500

UN No. (DOT) 3500

UN proper shipping name

Tensorgrip G67 Water-Based Pressure Sensitive Flooring Adhesive Canister

Proper shipping name (TDG) Chemical Under Pressure, N.O.S. (1,1,1,2 Tetraflouroethane)

Proper shipping name (DOT) Chemical Under Pressure, N.O.S. (1,1,1,2 Tetraflouroethane)

Transport hazard class(es)

TDG class 2

TDG label(s) 2.2

Transport labels



Packing group

Packing group (International) Not applicable.

15. Regulatory information

National regulations All applicable legislation listed in other parts of this Safety Data Sheet

Guidance Safety Data Sheets for Substances and Preparations.

US Federal Regulations

SARA (311/312) Hazard Categories

Present.

1,1,1,2 Tetraflouroethane (134a)

Pressure
Hazard
Acute
Health hazard

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

This product does not contain any chemicals known to the state of California to cause cancer, birth defects or any other reproductive harm.

New Jersey "Right To Know" List

1,1,1,2 Tetraflouroethane (134a)

Present.

Pennsylvania "Right To Know" List

1,1,1,2 Tetraflouroethane (134a)

Present.

Inventories

Canada - DSL/NDSL

The following ingredients are listed or exempt:

1,1,1,2 Tetraflouroethane (134a)

Present.

US - TSCA

The following ingredients are listed or exempt:

Tensorgrip G67 Water-Based Pressure Sensitive Flooring Adhesive Canister

1,1,1,2 Tetrafluoroethane (134a)

Present.

16. Other information

Revision date	1/16/2019
Revision	6
Supersedes date	8/20/2015
SDS No.	22586
Hazard statements in full	H280 Contains gas under pressure; may explode if heated. H302 Harmful if swallowed. H312 Harmful in contact with skin. H319 Causes serious eye irritation. H332 Harmful if inhaled. USH03 May displace oxygen and cause rapid suffocation
ACA HMIS Health rating.	Slight hazard. (1)
ACA HMIS Flammability rating.	Will not burn. (0)
ACA HMIS Physical hazard rating.	Normally stable. (0)
ACA HMIS Personal protection rating.	B

DIRECTIONS FOR USE

PRODUCT LOGO

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of this product, many of which are solely within the user's knowledge and control, the user is responsible for determining whether the usage of this product is fit for a particular purpose and suitable for the user's method of use or application. It is essential that the user, not the manufacturer, evaluates this product to determine whether it is fit for a particular purpose and suitable for the user's method of use or application.